



Features

1. 5.0 MP video quality
2. 3.6mm Lens
3. 2 way audio
4. IP66 waterproof rating
5. 3G/4G network
6. Humanoid motion detect
7. 7*24H video recording
8. Local storage TF card 128GB
9. Support CamHipro cloud storage

Item	B6-4G	
Image Sensor	Sensor	1/3" GC4653 CMOS T31X
	Resolution	2560x1920 (5.0MP)
	Lens	f: 3.6mm, F:2.0
	View angle	55°
	Mini. Illumination	0.01Lux
Audio	I/O	Built in MIC and SPEKER
	Audio compression	AAC
Video	Video Compression	H.265
	Light Frequency	50Hz, 60Hz
	Image frame rate	15fps
	Image resolution	5.0MP (2560x1920)
	Image adjustment	Adjustable brightness, contrast, saturation and sharpness
	Light control	Full Color / Smart / Infrared Factory default: Smart
	Night vision	6pcs Array IR LEDs
3G/4G Network	3G standard	WCDMA
	3G frequency range	B1(2100MHz), B8(900MHz)
	4G standard	FDD-LTE/TDD-LTE
	4G frequency range	B1(2100MHz),B3(1800MHz),B7(2600MHz), B8(900MHz),B20(800MHz),B38(2600MHz), B40(2300MHz),B41(2500MHz)
Alarm	Mobile detection	4 detection zones, support humanoid detect
	Alarm linkage	Snapshot, audio/video recording
	Alarm notification	Alarm message push
Interface	Power Supply	DC 12V / 2A
	Reset	Support
	Network interface	10/100Mbps RJ-45
	WiFi interface	External single WiFi antenna
Other	PTZ	N/A
	Storage	Micro SD card (up to 128GB) local storage
Environment	Working temperature	0° ~ 55°C (32°F ~ 131°F)
	Working humidity	10% ~ 80%
	Storage temperature	-10°C ~ 60° (14°F ~ 140°F)
	Storage humidity	0% ~ 90%